



P.O. BOX 3649 • CROSSVILLE, TN 38557 • (931) 484-9578 • FAX (931) 484-7614

## **BENCO #B24 INDUSTRIAL PAINT REMOVER**

### Description

Benco #B24 is a semi-paste, water rinsable remover capable of stripping many paints and finishes. #B24 will strip shellacs, varnishes, lacquers, polyurethanes, enamels, and acrylics. #B24 has a long wet life and will cling to vertical surfaces. #B24 is formulated with the highest quality solvents, surfactants, and additives.

### Characteristics

N-Methyl-2-Pyrrolidone Content	50-65% by weight
Specific Gravity	1.01 (8.41 lbs./gal.)
Percent Volatile	>95%
VOC Content	1006 grams/liter
Boiling Point (Initial)	329 degrees F
Freezing Point	Less than 30 F
Flash Point:	140 F
Shelf Life:	Minimum 1 year, unopened, stored at less than 75 F

### Application

Apply Benco #B24 by brush or roller, brushing in 1 direction only.

Apply a liberal coat and allow product to strip all coatings prior to removal. Thin coatings and clear finishes will usually strip in less than 60 minutes.

For items with multiple coatings, apply a liberal coat of stripper, and allow adequate time for the remover to penetrate to the substrate. In some applications, several hours may be required to penetrate multiple coatings. This product will remain wet and active for extended periods.

If the product has dried on the surface, reapply a coat of stripper prior to removal of finish for best results.

Stripped finishes can be removed with a scraper. Removed finishes with stripper can be reapplied to extend the life of the stripper.

For best results, once finishes are removed from the surface, rinse with water. Denatured alcohol can be used as an alternative to water.

Allow adequate time for the remover to completely evaporate from the surface prior to finishing.

Clean up with water.

Contact Benco at 800-632-3626 for technical assistance.